



# UNITED STATES PATENT AND TRADEMARK OFFICE

UNITED STATES DEPARTMENT OF COMMERCE  
United States Patent and Trademark Office  
Address: COMMISSIONER FOR PATENTS  
P.O. Box 1450  
Alexandria, Virginia 22313-1450  
www.uspto.gov

APPLICATION NO.	FILING DATE	FIRST NAMED INVENTOR	ATTORNEY DOCKET NO.	CONFIRMATION NO.
-----------------	-------------	----------------------	---------------------	------------------

10/573,462

03/24/2006

Takuya Kinoshita

NNA-241-B

2578

48980 7590 05/20/2010

YOUNG BASILE  
3001 WEST BIG BEAVER ROAD  
SUITE 624  
TROY, MI 48084

EXAMINER

CULLEN, SEAN P

ART UNIT

PAPER NUMBER

1795

NOTIFICATION DATE

DELIVERY MODE

05/20/2010

ELECTRONIC

**Please find below and/or attached an Office communication concerning this application or proceeding.**

The time period for reply, if any, is set in the attached communication.

Notice of the Office communication was sent electronically on above-indicated "Notification Date" to the following e-mail address(es):

docketing@youngbasile.com  
audit@youngbasile.com

<b>Office Action Summary</b>	<b>Application No.</b> 10/573,462	<b>Applicant(s)</b> KINOSHITA ET AL.	
	<b>Examiner</b> Sean P. Cullen	<b>Art Unit</b> 1795	

-- The MAILING DATE of this communication appears on the cover sheet with the correspondence address --

### Period for Reply

A SHORTENED STATUTORY PERIOD FOR REPLY IS SET TO EXPIRE 3 MONTH(S) OR THIRTY (30) DAYS, WHICHEVER IS LONGER, FROM THE MAILING DATE OF THIS COMMUNICATION.

- Extensions of time may be available under the provisions of 37 CFR 1.136(a). In no event, however, may a reply be timely filed after SIX (6) MONTHS from the mailing date of this communication.
- If NO period for reply is specified above, the maximum statutory period will apply and will expire SIX (6) MONTHS from the mailing date of this communication.
- Failure to reply within the set or extended period for reply will, by statute, cause the application to become ABANDONED (35 U.S.C. § 133). Any reply received by the Office later than three months after the mailing date of this communication, even if timely filed, may reduce any earned patent term adjustment. See 37 CFR 1.704(b).

### Status

- 1) ☒ Responsive to communication(s) filed on 12 April 2010.
- 2a) ☐ This action is **FINAL**.                      2b) ☒ This action is non-final.
- 3) ☐ Since this application is in condition for allowance except for formal matters, prosecution as to the merits is closed in accordance with the practice under *Ex parte Quayle*, 1935 C.D. 11, 453 O.G. 213.

### Disposition of Claims

- 4) ☒ Claim(s) 1,3-15 and 17-20 is/are pending in the application.
- 4a) Of the above claim(s) \_\_\_\_\_ is/are withdrawn from consideration.
- 5) ☐ Claim(s) \_\_\_\_\_ is/are allowed.
- 6) ☒ Claim(s) 1,3-15,17-20 is/are rejected.
- 7) ☐ Claim(s) \_\_\_\_\_ is/are objected to.
- 8) ☐ Claim(s) \_\_\_\_\_ are subject to restriction and/or election requirement.

### Application Papers

- 9) ☐ The specification is objected to by the Examiner.
- 10) ☐ The drawing(s) filed on \_\_\_\_\_ is/are: a) ☐ accepted or b) ☐ objected to by the Examiner.  
Applicant may not request that any objection to the drawing(s) be held in abeyance. See 37 CFR 1.85(a).  
Replacement drawing sheet(s) including the correction is required if the drawing(s) is objected to. See 37 CFR 1.121(d).
- 11) ☐ The oath or declaration is objected to by the Examiner. Note the attached Office Action or form PTO-152.

### Priority under 35 U.S.C. § 119

- 12) ☐ Acknowledgment is made of a claim for foreign priority under 35 U.S.C. § 119(a)-(d) or (f).
- a) ☐ All    b) ☐ Some \*    c) ☐ None of:
1. ☐ Certified copies of the priority documents have been received.
  2. ☐ Certified copies of the priority documents have been received in Application No. \_\_\_\_\_.
  3. ☐ Copies of the certified copies of the priority documents have been received in this National Stage application from the International Bureau (PCT Rule 17.2(a)).

\* See the attached detailed Office action for a list of the certified copies not received.

### Attachment(s)

- |   |   |
|---|---|
| 1) <input checked="" type="checkbox"/> Notice of References Cited (PTO-892)         | 4) <input type="checkbox"/> Interview Summary (PTO-413)           |
| 2) <input type="checkbox"/> Notice of Draftperson's Patent Drawing Review (PTO-948) | Paper No(s)/Mail Date. _____                                      |
| 3) <input type="checkbox"/> Information Disclosure Statement(s) (PTO/SB/08)         | 5) <input type="checkbox"/> Notice of Informal Patent Application |
| Paper No(s)/Mail Date _____   | 6) <input type="checkbox"/> Other: _____                          |

## **DETAILED ACTION**

### ***Continued Examination Under 37 CFR 1.114***

1. A request for continued examination under 37 CFR 1.114, including the fee set forth in 37 CFR 1.17(e), was filed in this application after final rejection. Since this application is eligible for continued examination under 37 CFR 1.114, and the fee set forth in 37 CFR 1.17(e) has been timely paid, the finality of the previous Office action has been withdrawn pursuant to 37 CFR 1.114. Applicant's submission filed on April 12, 2010 has been entered.

### ***Claim Rejections - 35 USC § 102***

2. The following is a quotation of the appropriate paragraphs of 35 U.S.C. 102 that form the basis for the rejections under this section made in this Office action:

A person shall be entitled to a patent unless –

(e) the invention was described in (1) an application for patent, published under section 122(b), by another filed in the United States before the invention by the applicant for patent or (2) a patent granted on an application for patent by another filed in the United States before the invention by the applicant for patent, except that an international application filed under the treaty defined in section 351(a) shall have the effects for purposes of this subsection of an application filed in the United States only if the international application designated the United States and was published under Article 21(2) of such treaty in the English language.

3. Claims 1, 3, 5, 11-15, 17, 19 and 20 are rejected under 35 U.S.C. 102(e) as being anticipated by Nagayama et al. (U.S. 2005/0208347).

Regarding claim 1, Nagayama et al. discloses a bipolar battery cell (10) comprising:

- a plurality of electric cells (20), each electric cell comprising:
  - a bipolar electrodes (30), including
  - a collector (22) having
    - a positive-electrode layer (28) on one surface and

Art Unit: 1795

- a negative-electrode layer (26) on an opposing surface (Fig. 3, [0034]);
- an electrolyte layer (27) that exchange ions between the positive-electrode layer (28) and the negative electrode layer (26, Fig. 4); and
- a discharge circuit (50) printed on one or more of the positive-electrode layer (28), the negative electrode layer (26) and electrolyte layer (27) within each electric cell (40, Fig. 4)
- the discharge circuit (50) configured within each bipolar electrode (30) to electrically balance charged conditions ([0037]-[0039]) of adjacent electric cells (40).

Regarding claim 3, Nagayama et al. discloses all claim limitations set forth above and further discloses a bipolar battery cell:

- a contact area between the discharge circuit (50) and the bipolar electrode (30) that is more than  $0.06 \text{ mm}^2$  per battery capacity of the bipolar battery 1 Ah (see  $0.2 \text{ cm} \times 0.1 \text{ cm}$ , [0097]; 202 mAh, [0104];  $1000 \text{ mm}^2/\text{Ah}$ ).

Regarding claim 5, Nagayama et al. discloses all claim limitations set forth above and further discloses a bipolar battery cell:

Art Unit: 1795

- wherein the discharge circuit (50) includes a zener diode layer (32).

Regarding claim 11, Nagayama et al. discloses all claim limitations set forth above and further discloses a bipolar battery cell:

- further comprising a sheathing material (16) that covers and seals the bipolar electrodes (30), the electrolyte layers (27), and the discharge circuit (50, Fig. 2).

Regarding claim 12, Nagayama et al. discloses all claim limitations set forth above and further discloses a bipolar battery cell:

- further comprising a conductive sealing material (36, [0036]).

Regarding claim 13, Nagayama et al. discloses an assembled battery (70) comprising:

- a plurality of bipolar battery cells (10, Fig. 15C),
- wherein each bipolar battery cell (10) comprises:
  - a plurality of electric cells (20) each electric cell comprising:
  - a laminated bipolar electrodes (30) including
    - a collector (22) having
      - a positive-electrode layer (28) on one surface and
      - a negative-electrode layer (26) on an opposing surface (Fig. 3, [0034]);
  - a electrolyte layer (27) that exchange ions between the positive-electrode layer (28) and the negative electrode layer (26, Fig. 4); and
  - a discharge circuit (50) printed on one or more of the positive-electrode layer (28), the negative electrode layer (26) and electrolyte layer (27, Fig.

Art Unit: 1795

4) that electrically balances charged conditions ([0037]-[0039]) of adjacent bipolar electrodes (30).

Regarding claim 14, Nagayama et al. discloses a vehicle (80) comprising:

- a controller (see control circuit, [0083]); and
- an assembled bipolar battery (70) comprising
  - a plurality of bipolar battery cells (10), wherein each bipolar battery cell (10) comprises:
    - a plurality of electric cells (20), each electric cell (20) comprising
      - a bipolar electrode (30) including
      - a collector (22) having
        - a positive-electrode layer (28) on one surface and
        - a negative-electrode layer (26) on an opposing surface (Fig. 3, [0034]);
      - an electrolyte layers (27) that exchange ions between the positive-electrode layer (28) and the negative electrode layer (26, Fig. 4) and
      - a discharge circuit (50) printed on one or more of the positive-electrode layer (28), the negative electrode layer (26) and electrolyte layer (27) that electrically balances charged conditions ([0037]-[0039]) of adjacent bipolar electrodes (30).

Art Unit: 1795

Regarding claim 15 Nagayama et al. discloses a method of forming a bipolar battery cell

(10) each bipolar battery cell (10) comprising a plurality of electric cells (20) comprising:

- laminating [0033] a bipolar electrodes (30) including
  - a collector (22) having
    - positive-electrode layer (28) on one surface and
    - a negative-electrode layer (26) on an opposing surface (Fig. 3, [0034]);
- with an electrolyte layer (27) that exchange ions between the positive-electrode layer (28) and the negative electrode layer (26, Fig. 4); and
- a discharge circuit (50) printed on one or more of the positive-electrode layer (28), the negative electrode layer (26) and electrolyte layer (27, Fig. 4) that electrically balance charged conditions ([0037]-[0039]) of adjacent bipolar electrodes (30) to form each electric cell (20) of the plurality of electric cells (10).

Regarding claim 17, Nagayama et al. discloses a bipolar battery cell (10) comprising:

- a plurality of electric cells (20), each electric cell (20) comprising:
  - a bipolar electrode (30) including
    - a collector (22) having
      - a positive-electrode layer (28) on one surface and
      - a negative-electrode layer (26) on an opposing surface (Fig. 3, [0034]);
  - a means for exchanging ions (27) between the positive-electrode layer (28) and the negative electrode layer (26, Fig. 4); and

Art Unit: 1795

- a means for balancing the bipolar battery cell (50) by electrically balances charged conditions ([0037]-[0039]) of adjacent bipolar electrodes (30),
- the means for balancing (50) located on one or more of the positive-electrode layer (28), the negative electrode layer (26) and electrolyte layer (27, Fig. 4).

Regarding claim 19, Nagayama et al. discloses all claim limitations set forth above and further discloses a bipolar battery cell:

- wherein each electric cell (20) further comprises
  - conductive bodies (22A and 22B) printed on each of the positive-electrode layer (28), the negative electrode layer (26) and electrolyte layer (27, Fig. 4),
  - wherein the discharge circuit (50) is located directly between two conductive bodies (22A and 22B, Fig. 4).

Regarding claim 20, Nagayama et al. discloses all claim limitations set forth above and further discloses a bipolar battery cell:

- wherein the conductive bodies (22A and 22B) located on each of the positive-electrode layer (28), the negative electrode layer (26) and electrolyte layer (27) are positioned such that the conductive bodies (22A and 22B) electrically conduct with adjacent conductive bodies (22A and 22B, Fig. 4).



Art Unit: 1795

***Claim Rejections - 35 USC § 103***

4. The text of those sections of Title 35, U.S. Code not included in this action can be found in a prior Office action.

5. Claim 4 is rejected under 35 U.S.C. 103(a) as being unpatentable over Nagayama et al. (U.S. 2005/0208347) as applied to claim 1 above, and further in view of Einthoven et al. (U.S. 2003/0205775).

Regarding claim 4, Nagayama et al. discloses all claim limitations set forth above and further discloses a bipolar battery cell:

- wherein a threshold of a discharge voltage in the discharge circuit is set between 3.6 V-4.1 V (see 4 V, [0039]), and

Nagayama et al. does not explicitly disclose:

- wherein a doping concentration is set between  $10^{17}$ - $10^{18}$  cm<sup>-3</sup>, and
- the thickness of a depletion layer is set between 0.1 μm-1.0 μm so as to set a breakdown voltage of a PN-junction of the discharge circuit the same as to the threshold.

Einthoven et al. discloses a voltage suppression device (abstract) with a doping concentration  $10^{17}$ - $10^{18}$  cm<sup>-3</sup> (see  $2 \times 10^{17}$ - $2 \times 10^{18}$  cm<sup>-3</sup>, [0051]) and the thickness of a depletion layer is set between 0.1 μm-1.0 μm (see 0.2 μm, [0035]) to control the breakdown voltage of the device [0048]. Nagayama et al. and Einthoven et al. are analogous art because they are directed to voltage suppression devices (solid state semiconductor). Therefore, it would have been obvious to one of ordinary skill in the art at the time of the invention to make the bipolar battery

Art Unit: 1795

cell of modified Horie et al. using the voltage suppression device of Einthoven to control the breakdown voltage.

6. Claims 6-10 and 18 rejected under 35 U.S.C. 103(a) as being unpatentable over Nagayama et al. (U.S. 2005/0208347) as applied to claims 1 above, and further in view of Horie et al. (U.S. 2001/0019794).

Regarding claims 6-10 and 18, Nagayama et al. discloses all claim limitations set forth above and further discloses a bipolar battery cell:

- further comprising a sheathing material (16) that covers and seals the bipolar electrodes (30), the electrolyte layers (27) and the discharge circuit (50, Fig. 2)
- wherein the discharge circuit (50) comprises a voltage balancing circuit (50, [0037]-[0039]).

Nagayama et al. does not explicitly disclose:

- wherein the discharge circuit includes a luminescent device.
- further comprising a light guiding device arranged between the luminescent device and an end of the battery cell.
- further comprising a light sensor that responds to light emitted from the relevant luminescent device.
- wherein the discharge circuit includes a constant current circuit.
- further comprising a sheathing material that covers and seals the light sensor.

Horie et al. discloses a bipolar battery cell (see cell group of a battery, abstract) wherein the discharge circuit (1) includes a luminescent device (see luminescent element, Fig. 1); further

Art Unit: 1795

comprising a light guiding device (12) arranged between the luminescent device (11) and an end of the battery cell (Fig. 8); further comprising a light sensor (4) that responds to light emitted from the relevant luminescent device (11, [0065]); wherein the discharge circuit (1) includes a constant current circuit (20, Fig. 9A); wherein the discharge circuit (1) includes a constant current circuit (20, Fig. 9A); and wherein the discharge circuit comprises an abnormal voltage detecting circuit (4 and 12) to sense the voltage of the battery cells without the need of complex circuitry and reduce the current consumption of the discharge circuit [0010] to increase the energy density and efficiency of the battery. Nagayama et al. and Horie et al. are analogous art because they are directed to bipolar battery cell assemblies. Therefore, it would have been obvious to one of ordinary skill in the art at the time of the invention to make the bipolar battery cell of Nagayama et al. with the luminescent device, light guiding device and light sensor of Horie et al. to sense the voltage of the battery cells without the need of complex circuitry and reduce the current consumption of the discharge circuit to increase the energy density and efficiency of the battery.

7. Claims 1, 3, 5, 11-15, 17, 19 and 20 are rejected under 35 U.S.C. 103(a) as being unpatentable over Hisamitsu et al. (U.S. 2004/0038123) in view of Nakanaga et al. (JP 02044660, see English-language abstract).

Art Unit: 1795

Regarding claims 1 and 11, Hisamitsu et al. discloses a bipolar battery cell (1) comprising:

- a plurality of electric cells (Fig. 3), each electric cell comprising:
  - a bipolar electrodes (30), including
    - a collector (31) having
      - a positive-electrode layer (32) on one surface and
      - a negative-electrode layer (33) on an opposing surface (Fig. 3);
    - an electrolyte layer (40) that exchange ions between the positive-electrode layer (32) and the negative electrode layer (33, Fig. 3; [0079]); and
    - a discharge circuit (50)
    - the discharge circuit (50) configured within each bipolar electrode (30) to electrically balance charged conditions of adjacent electric cells ([0123]-[0125]).
  - further comprising a sheathing material (45) that covers and seals the bipolar electrodes (30) and the electrolyte layers (40).

Hisamitsu et al. does not explicitly disclose:

- a discharge circuit printed on one or more of the positive-electrode layer, the negative electrode layer and electrolyte layer within each electric cell.
- a sheathing material that covers and seals the discharge circuit

Art Unit: 1795

Nakanaga et al. discloses a bipolar battery cell (Drawing 4) comprising a discharge circuit (9) printed on one or more of the positive-electrode layer (3 and 7), the negative electrode layer (5) and electrolyte layer (6) within each electric cell (Drawing 4) in order to provide a discharge circuit that is a single piece unit there by allowing for ease of assembly of the bipolar battery cell. Hisamitsu et al. and Nakanaga et al. are analogous art because they are directed to battery cells with discharge circuits. Therefore, it would have been obvious to one of ordinary skill in the art at the time of the invention to make the bipolar battery cell of Hisamitsu et al. with the configuration of Nakanaga et al. in order to provide a discharge circuit that is a single piece unit there by allowing for ease of assembly of the bipolar battery cell.

It further would have been obvious to integrate the discharge circuit of Hisamitsu et al. into the electrical cell; since, it has been held that forming in one piece an article has formerly been formed in two pieces and put together involves only routine skill in the art. *Howard v. Detroit Stove Works*, 150 U.S. 164 (1893).

If a technique has been used to improve one device (integrating a discharge circuit into an electric cell) and a person of ordinary skill in the art would recognize that it would improve similar devices in the same way (providing a discharge circuit that is a single piece unit thereby allowing for ease of assembly of the battery cell), using the technique is obvious unless its actual application is beyond his or her skill. See MPEP § 2141 (III) Rational C from *KSR v. Teleflex* (Supreme Court 2007).

Regarding claim 3, modified Hisamitsu et al. discloses all claim limitations set forth above, but does not explicitly disclose a bipolar battery cell:

Art Unit: 1795

- a contact area between the discharge circuit and the bipolar electrode that is more than  $0.06 \text{ mm}^2$  per battery capacity of the bipolar battery 1 Ah.

As the size of the opening for the discharge circuit and thickness of discharge circuit are variables that can be modified, among others, by adjusting the contact area between the discharge circuit and the bipolar electrode, with the opening for the discharge circuit increasing and the thickness of the discharge circuit decreasing as the contact area is increased (Nakanaga et al., Drawing 4), the contact area would have been considered a result effective variable by one having ordinary skill in the art at the time the invention was made. As such, without showing unexpected results, the claimed contact area cannot be considered critical. Accordingly, one of ordinary skill in the art at the time the invention was made would have optimized, by routine experimentation, the contact area in the bipolar battery cell of modified Hisamitsu et al. to obtain the desired balance between the size of the opening of the discharge circuit and the thickness of the discharge circuit (*In re Boesch*, 617 F.2d. 272, 205 USPQ 215 (CCPA 1980)), since it has been held that where the general conditions of the claim are disclosed in the prior art, discovering the optimum or workable ranges involves only routine skill in the art. (*In re Aller*, 105 USPQ 223).

Regarding claim 5, modified Hisamitsu et al. discloses all claim limitations set forth above and further discloses a bipolar battery cell:

- wherein the discharge circuit (50) includes a zener diode layer (52).

Regarding claim 12, modified Hisamitsu et al. discloses all claim limitations set forth above and further discloses a bipolar battery cell:

- further comprising a conductive sealing material (45, [0050]).

Art Unit: 1795

Regarding claim 13, Hisamitsu et al. discloses an assembled battery (Fig. 3) comprising:

- a plurality of bipolar battery cells (see plurality of bipolar batteries, [0148]),
- wherein each bipolar battery cell (Fig. 3) comprises:
  - a plurality of electric cells (Fig. 3) each electric cell comprising:
  - a laminated bipolar electrodes (30) including
    - a collector (31) having
      - a positive-electrode layer (32) on one surface and
      - a negative-electrode layer (33) on an opposing surface (Fig. 3);
  - a electrolyte layers (40) that exchange ions between the positive-electrode layer (32) and the negative electrode layer (33, [0079]); and
  - a discharge circuit (50) that electrically balances charged conditions of adjacent bipolar electrodes (30, [0123]-[0125]).

Hisamitsu et al. does not explicitly disclose:

- a discharge circuit printed on one or more of the positive-electrode layer, the negative electrode layer and electrolyte layer

Nakanaga et al. discloses a bipolar battery cell (Drawing 4) comprising a discharge circuit (9) printed on one or more of the positive-electrode layer (3 and 7), the negative electrode layer (5) and electrolyte layer (6) within each electric cell (Drawing 4) in order to provide a discharge circuit that is a single piece unit there by allowing for ease of assembly of the bipolar battery cell. Therefore, it would have been obvious to one of ordinary skill in the art at the time of the invention to make the bipolar battery cell of Hisamitsu et al. with the configuration of

Art Unit: 1795

Nakanaga et al. in order to provide a discharge circuit that is a single piece unit there by allowing for ease of assembly of the bipolar battery cell.

Regarding claim 14, Hisamitsu et al. discloses a vehicle (801) comprising:

- a controller (see unit cell controller, [0147]); and
- an assembled bipolar battery (800) comprising
  - a plurality of bipolar battery cells (see plurality of bipolar batteries, [0148]), wherein each bipolar battery cell (see stack type battery, abstract) comprises:
    - a plurality of electric cells, each electric cell comprising
      - a bipolar electrode (30) including
      - a collector (31) having
        - a positive-electrode layer (32) on one surface and
        - a negative-electrode layer (33) on an opposing surface (Fig. 3);
      - an electrolyte layers (40) that exchange ions between the positive-electrode layer (32) and the negative electrode layer (33, [0079]) and
      - a discharge circuit (50) that electrically balances charged conditions of adjacent bipolar electrodes (30, [0123]-[0125]),

Hisamitsu et al. does not explicitly disclose:



Art Unit: 1795

- a discharge circuit printed on one or more of the positive-electrode layer, the negative electrode layer and electrolyte layer

Nakanaga et al. discloses a bipolar battery cell (Drawing 4) comprising a discharge circuit (9) printed on one or more of the positive-electrode layer (3 and 7), the negative electrode layer (5) and electrolyte layer (6) within each electric cell (Drawing 4) in order to provide a discharge circuit that is a single piece unit there by allowing for ease of assembly of the bipolar battery cell. Therefore, it would have been obvious to one of ordinary skill in the art at the time of the invention to make the bipolar battery cell of Hisamitsu et al. with the configuration of Nakanaga et al. in order to provide a discharge circuit that is a single piece unit there by allowing for ease of assembly of the bipolar battery cell.

Regarding claim 15, Hisamitsu et al. discloses a method of forming a bipolar battery cell (Fig. 3) each bipolar battery cell (Fig. 3) comprising a plurality of electric cells (Fig. 3) comprising:

- laminating a bipolar electrodes (340, [0047]) including
  - a collector (31) having
    - positive-electrode layer (32) on one surface and
    - a negative-electrode layer (33) on an opposing surface (Fig. 3);
- with an electrolyte layer (40) that exchange ions between the positive-electrode layer (32) and the negative electrode layer (33, Fig. 3; [0047] and [0079]); and
- a discharge circuit (50) that electrically balance charged conditions of adjacent bipolar electrodes (30) to form each electric cell of the plurality of electric cells (Fig. 3, [0123]-[0125]).

Art Unit: 1795

Hisamitsu et al. does not explicitly disclose:

- a discharge circuit printed on one or more of the positive-electrode layer, the negative electrode layer and electrolyte layer

Nakanaga et al. discloses a bipolar battery cell (Drawing 4) comprising a discharge circuit (9) printed on one or more of the positive-electrode layer (3 and 7), the negative electrode layer (5) and electrolyte layer (6) within each electric cell (Drawing 4) in order to provide a discharge circuit that is a single piece unit there by allowing for ease of assembly of the bipolar battery cell. Therefore, it would have been obvious to one of ordinary skill in the art at the time of the invention to make the bipolar battery cell of Hisamitsu et al. with the configuration of Nakanaga et al. in order to provide a discharge circuit that is a single piece unit there by allowing for ease of assembly of the bipolar battery cell.

Regarding claim 17, Hisamitsu et al. discloses a bipolar battery cell (Fig. 3) comprising:

- a plurality of electric cells (Fig. 3), each electric cell comprising:
  - a bipolar electrode (30) including
    - a collector (31) having
      - a positive-electrode layer (32) on one surface and
      - a negative-electrode layer (33) on an opposing surface (Fig. 3);
  - a means for exchanging ions (40) between the positive-electrode layer (32) and the negative electrode layer (33, [0079]); and
  - a means for balancing the bipolar battery cell (50) by electrically balances charged conditions of adjacent bipolar electrodes (30, [0123]-[0125])),

Art Unit: 1795

Hisamitsu et al. does not explicitly disclose:

- the means for balancing located on one or more of the positive-electrode layer, the negative electrode layer and electrolyte layer.

Nakanaga et al. discloses a bipolar battery cell (Drawing 4) comprising a discharge circuit (9) printed on one or more of the positive-electrode layer (3 and 7), the negative electrode layer (5) and electrolyte layer (6) within each electric cell (Drawing 4) in order to provide a discharge circuit that is a single piece unit there by allowing for ease of assembly of the bipolar battery cell. Therefore, it would have been obvious to one of ordinary skill in the art at the time of the invention to make the bipolar battery cell of Hisamitsu et al. with the configuration of Nakanaga et al. in order to provide a discharge circuit that is a single piece unit there by allowing for ease of assembly of the bipolar battery cell.

Regarding claim 19, modified Hisamitsu et al. discloses all claim limitations set forth above and further discloses a bipolar battery cell:

- wherein each electric cell (Fig. 3) further comprises conductive bodies (31) printed on each of the positive-electrode layer (32), the negative electrode layer (33) and electrolyte layer (40, Fig. 3),

Hisamitsu et al. does not explicitly disclose:

- wherein the discharge circuit is located directly between two conductive bodies.

Nakanaga et al. discloses a bipolar battery cell (Drawing 4) wherein a discharge circuit (3 and 7) is located directly between two conductive bodies (1 and 8, Drawing 4) in order to provide a discharge circuit that is a single piece unit there by allowing for ease of assembly of the bipolar battery cell. Therefore, it would have been obvious to one of ordinary skill in the art

Art Unit: 1795

at the time of the invention to make the bipolar battery cell of Hisamitsu et al. with the configuration of Nakanaga et al. in order to provide a discharge circuit that is a single piece unit there by allowing for ease of assembly of the bipolar battery cell.

Regarding claim 20, modified Hisamitsu et al. discloses all claim limitations set forth above and further discloses a bipolar battery:

- wherein the conductive bodies (31) located on each of the positive-electrode layer (32), the negative electrode layer (33) and electrolyte layer (40) are positioned such that the conductive bodies (31) electrically conduct with adjacent conductive bodies (Fig. 2).

8. Claim 4 is rejected under 35 U.S.C. 103(a) as being unpatentable over Hisamitsu et al. (U.S. 2004/0038123) in view of Nakanaga et al. (JP 02044660, see English-language abstract) as applied to claim 1 above, and further in view of Einthoven (U.S. 2003/0205775).

Regarding claim 4, modified Hisamitsu et al. discloses all claim limitations set forth above and further discloses a bipolar battery cell:

- wherein a threshold of a discharge voltage in the discharge circuit is set between 3.6 V-4.1 V (see 4.0 V, [0124]), and

Hisamitsu et al. does not explicitly disclose:

- wherein a doping concentration is set between  $10^{17}$ - $10^{18}$  cm<sup>-3</sup>, and
- the thickness of a depletion layer is set between 0.1 μm-1.0 μm so as to set a breakdown voltage of a PN-junction of the discharge circuit the same as to the threshold.

Art Unit: 1795

Eindhoven et al. discloses a voltage suppression device (abstract) with a doping concentration  $10^{17}$ - $10^{18}$   $\text{cm}^{-3}$  (see  $2 \times 10^{17}$ - $2 \times 10^{18}$   $\text{cm}^{-3}$ , [0051]) and the thickness of a depletion layer is set between 0.1  $\mu\text{m}$ -1.0  $\mu\text{m}$  (see 0.2  $\mu\text{m}$ , [0035]) to control the breakdown voltage of the device [0048]. Hisamitsu et al. and Eindhoven et al. are analogous art because they are directed to voltage suppression devices (solid state semiconductor). Therefore, it would have been obvious to one of ordinary skill in the art at the time of the invention to make the bipolar battery cell of modified Hisamitsu et al. using the voltage suppression device of Eindhoven to control the breakdown voltage.

9. Claims 6-10 and 18 are rejected under 35 U.S.C. 103(a) as being unpatentable over Hisamitsu et al. (U.S. 2004/0038123) in view of Nakanaga et al. (JP 02044660, see English-language abstract) as applied to claims 1 above, and further in view of Horie et al. (U.S. 2001/0019794).

Regarding claims 6-10 and 18, modified Hisamitsu et al. discloses all claim limitations set forth above and further discloses a bipolar battery cell:

- further comprising a sheathing material (45) that covers and seals the bipolar electrodes (30) and the electrolyte layers (40, Fig. 3)
- wherein the discharge circuit (50) comprises a voltage balancing circuit ([0123]-[0125]).

Nagayama et al. does not explicitly disclose:

- wherein the discharge circuit includes a luminescent device.

Art Unit: 1795

- further comprising a light guiding device arranged between the luminescent device and an end of the battery cell.
- further comprising a light sensor that responds to light emitted from the relevant luminescent device.
- wherein the discharge circuit includes a constant current circuit.
- further comprising a sheathing material that covers and seals the light sensor and the discharge circuit.

Horie et al. discloses a bipolar battery cell (see cell group of a battery, abstract) wherein the discharge circuit (1) includes a luminescent device (see luminescent element, Fig. 1); further comprising a light guiding device (12) arranged between the luminescent device (11) and an end of the battery cell (Fig. 8); further comprising a light sensor (4) that responds to light emitted from the relevant luminescent device (11, [0065]); wherein the discharge circuit (1) includes a constant current circuit (20, Fig. 9A); wherein the discharge circuit (1) includes a constant current circuit (20, Fig. 9A); and wherein the discharge circuit comprises an abnormal voltage detecting circuit (4 and 12) to sense the voltage of the battery cells without the need of complex circuitry and reduce the current consumption of the discharge circuit [0010] to increase the energy density and efficiency of the battery. Nagayama et al. and Horie et al. are analogous art because they are directed to bipolar battery cell assemblies. Therefore, it would have been obvious to one of ordinary skill in the art at the time of the invention to make the bipolar battery cell of Nagayama et al. with the luminescent device, light guiding device and light sensor of Horie et al. to sense the voltage of the battery cells without the need of complex circuitry and

Art Unit: 1795

reduce the current consumption of the discharge circuit to increase the energy density and efficiency of the battery.

### ***Response to Arguments***

10. Applicant's arguments with respect to claims 1, 3-15 and 17-20 have been considered but are moot in view of the new ground(s) of rejection.

### ***Conclusion***

11. Any inquiry concerning this communication or earlier communications from the examiner should be directed to Sean P. Cullen whose telephone number is 571-270-1251. The examiner can normally be reached on Monday thru Thursday 6:30 a.m. to 5:00 p.m.

If attempts to reach the examiner by telephone are unsuccessful, the examiner's supervisor, Basia Ridley can be reached on 571-272-1453. The fax phone number for the organization where this application or proceeding is assigned is 571-273-8300.

Information regarding the status of an application may be obtained from the Patent Application Information Retrieval (PAIR) system. Status information for published applications may be obtained from either Private PAIR or Public PAIR. Status information for unpublished applications is available through Private PAIR only. For more information about the PAIR system, see <http://pair-direct.uspto.gov>. Should you have questions on access to the Private PAIR system, contact the Electronic Business Center (EBC) at 866-217-9197 (toll-free). If you would like assistance from a USPTO Customer Service Representative or access to the automated information system, call 800-786-9199 (IN USA OR CANADA) or 571-272-1000.

Application/Control Number: 10/573,462

Page 23

Art Unit: 1795

/S. P. C./

Examiner, Art Unit 1795

/Robert Hodge/

Primary Examiner, Art Unit 1795